

INSPIRE™

- Small-diameter, micro-smooth carbon finish
- Available in seven sizes
- One-piece points
- Parallel design

POINTS • INSERTS • NOCKS



Target Point
(50/75 gr.)



G Nock™ 4 MM
(7 gr.)



X Nock™ 4 MM
(9 gr.)



Steel Target Point
(70 gr. for 1400-2000 sizes)

IW SIZES

SPECIFICATIONS

| Size | Shaft Weight | Spine @ 28" Span | Minimum Stock Length | Glue-In Point | Nock |
|------|-----------------|----------------------|--------------------------------|---------------|------|
| | Grains per Inch | Deflection in Inches | Inches | Grains | |
| 2000 | 3.4 | 2.000 | 28 ¹ / ₄ | 70 | G |
| 1800 | 3.6 | 1.800 | 28 ¹ / ₂ | 70 | G |
| 1600 | 3.8 | 1.600 | 28 ³ / ₄ | 70 | G |
| 1400 | 4.2 | 1.400 | 29 | 50 | G |
| 1200 | 7.2 | 1.200 | 27 ¹ / ₄ | 50 | G |
| 1000 | 7.2 | 1.000 | 27 ¹ / ₂ | 50 | G |
| 900 | 7.7 | 0.900 | 28 ¹ / ₂ | 50 | G |
| 750 | 8.1 | 0.750 | 29 ¹ / ₂ | 50 | G |
| 630 | 7.9 | 0.630 | 30 ¹ / ₂ | 75 | X |
| 570 | 8.2 | 0.570 | 31 ¹ / ₂ | 75 | X |

